Page 1 of 7

MATERIAL SAFETY DATA SHEET

Supplier's name and address:

Refer to Manufacturer

Section 1 - Identification

Manufacturer's name and address:

HENRY

The W.W. Henry Company

400 Ardex Park Drive Aliquippa, PA, U.S.A.

15001

Information Telephone No. : (724) 203-8499

Visit our Website: http://www.wwhenry.com

24 Hr. Emergency Tel # : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

Product Identifier : Henry® 356C MultiPro™ Premium Commercial Multipurpose

Carpet and Sheet Vinyl Adhesive

 Chemical Name
 : N/Ap
 Chemical Family
 : Mixture.

 Chemical Formula
 : N/Ap
 Trade Name/Synonyms
 : Henry® 356C

Molecular Weight : N/Ap Material Use : Adhesive for installation

of Felt-backed Vinyl Sheet and Carpet.

HMIS Rating : *- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: *2 Flammability: 1 Reactivity: 0

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS classification:

Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material); Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

OSHA: This material is classified as hazardous under OSHA regulations (29CFR

1910.1200). Hazardous classification:

Chronic Health Hazard.

Emergency overview: : Beige, creamy paste. Mild odour.

Warning! May be mildly irritating to eyes and skin. May cause allergic respiratory

reaction. May cause allergic skin reaction.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation: Inhalation of mist causes irritation of respiratory system.

Skin : Direct skin contact may cause slight or mild, transient irritation.

Eyes : May cause mild transient irritation.

Ingestion : Ingestion of large amounts may cause stomach irritation. May cause nausea, vomiting, and diarrhea.

Effects of long-term (chronic) exposure

: Prolonged skin contact may cause skin irritation.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : Possible sensitizer. See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	CAS#	Wt.%
Kaolin	1332-58-7	7.00 - 13.00

 Urea
 57-13-6
 1.00 - 5.00

 Rosin
 8050-09-7
 1.00 - 5.00

 Solvent refined heavy paraffinic distillate
 64741-88-4
 5.00 - 10.00

 Distillates (petroleum), solvent-refined
 64741-89-5
 0.50 - 1.50

 Trisodium phosphate
 7601-54-9
 0.10 - 1.00

Note:: This product does NOT contain asbestos.

SECTION 4 - FIRST AID MEASURES

Inhalation : If inhaled, move to fresh air. If breathing has stopped, give artificial respiration. If

breathing is difficult, give oxygen by qualified medical personnel only. Get medical

attention

Skin contact: Remove contaminated clothing. Wash off with soap and plenty of water. Get medical attention. Launder clothing before reuse.

Eye contact : Flush with plenty of water. If irritation persists, seek prompt medical attention.

Ingestion : Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

Get medical attention.

Notes For Physician : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

: Not flammable under normal conditions of use. Closed containers may rupture if

exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.1200)

: Non-flammable.

Oxidizing properties : None.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Suitable extinguishing media : Dry chemical, foam, carbon dioxide and water fog.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all

equipment and surfaces exposed to fumes.

Hazardous combustion products

: Carbon oxides; nitrogen oxides (NOx); Sulphur oxides; Phosphorus compounds;

Hydrocarbons; Aldehydes; other unidentified organic compounds.

NFPA Rating 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

: Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions : Restrict access to area until completion of clean-up. All persons dealing with clean-up

should wear the appropriate chemically protective equipment. Refer to point 8 on this Safety Data Sheet, EXPOSURE CONTROLS / PERSONAL PROTECTION, for

additional information on acceptable personal protective equipment.

Environmental precautions : Do not allow product to enter waterways. Do not allow material to contaminate ground

water system.

Spill response/cleanup : Ventilate area of release. Eliminate all ignition sources. Stop spill or leak at source if

safely possible. Contain material, preventing it from entering sewer lines or waterways. Use inert, non-combustible absorbents to assist the pick up of material. Scrape up product and place it into a container for disposal. Refer to Section 13 for disposal of contaminated material. Residual of product, while still wet, can be cleaned up with

warm soapy water. Notify the appropriate authorities as required.

Prohibited materials : None known.

Special spill response procedures

Page 2 of 7

Page 3 of 7

: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).

US CERCLA Reportable quantity (RQ): None reported.

SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures

Wear suitable protective equipment during handling. Use with adequate ventilation. Training the workers on the potential health hazards associated with product vapor, dust or fume is important. Secondary inhalation exposures could occur when cleaning equipment, or when removing or laundering the clothing. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Keep away from oxidizing materials. Keep containers tightly closed when not in use. Wash thoroughly after handling.

Storage requirements

Store in a cool, dry, well-ventilated area. No smoking in the area. Do not store near any incompatible materials (see Section 10). Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Protect against physical damage.

Incompatible materials

See Section 10.

Special packaging materials

: Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits						
	ACGIH TLV		OSHA PEL			
<u>Ingredients</u>	<u>TWA</u>	STEL	PEL	<u>STEL</u>		
Kaolin	2 mg/m³ (respirable dust)	N/Av	15 mg/m³ (total dust); 5 mg/m³ (respirable fraction)	N/Av		
Urea	10 mg/m³ (AIHA WEEL)	N/Av	N/Av	N/Av		
Rosin	N/Av	N/Av	N/Av	N/Av		
Solvent refined heavy paraffinic distillate	5 mg/m³ (As 'Oil mist, mineral')	10 mg/m³ (As 'Oil mist, mineral')	5 mg/m³ (As 'Oil mist, mineral')	N/Av		
Distillates (petroleum), solvent-refined	5 mg/m³ (As 'Oil mist, mineral')	10 mg/m³ (As 'Oil mist, mineral')	5 mg/m³ (As 'Oil mist, mineral')	N/Av		
Trisodium phosphate	N/Av	5 mg/m³ (AIHA WEEL)	N/Av	N/Av		

Ventilation and engineering measures

: Use in a well-ventilated area. Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

Respiratory protection is required if the concentrations exceed the TLV.
 NIOSH-approved respirators are recommended. Advice should be sought from respiratory protection specialists.

Skin protection

: Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.

Eye / face protection

: If splashing might occur, wear eye protection such as safety glasses with side shields.

Other protective equipment

Wear sufficient clothing to prevent skin contact. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Do not eat, drink or smoke when using this product. Clean all equipment and clothing at end of each work shift.

MSDS Revision Date (dd/mm/yyyy): 27/10/2009

Page 4 of 7

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state : paste Appearance : Beige, creamy paste

Odour : Mild odour. Odour threshold : N/Av

pH : 9.2

 Boiling point
 : N/Av
 Specific gravity
 : 1.13

 Melting/Freezing point
 : N/Av
 Coefficient of water/oil distribution

: N/Av

Vapour pressure (mmHg @ 20° C / 68° F) Solubility in water : Miscible

: N/Av

Vapour density (Air = 1) : N/Av Evaporation rate (n-Butyl acetate = 1)

: N/Av

Volatile organic Compounds (VOC's)

Volatiles (% by weight) : 53%

: 1.7 g/L

Particle size : N/Av General Info. : No additional information.

Flash point : N/Av

Flash point Method : N/Av Auto-ignition temperature : N/Av

Lower flammable limit (% by vol.)

Upper flammable limit (% by vol.)

: Not applicable. : Not applicable.

Flame Projection Length : Not applicable. Flashback observed : Not applicable.

SECTION 10 - REACTIVITY AND STABILITY DATA

Stability and reactivity : Stable under the recommended storage and handling conditions prescribed.

Hazardous polymerization : Hazardous polymerisation does not occur.

Conditions to avoid : Extreme heat.

Materials To Avoid And Incompatibility

: Oxidizing agents; Acids .

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs : Eyes, skin, respiratory system and digestive system.

Routes of exposure : Inhalation: YES Skin Absorption: NO Skin & Eyes: YES Ingestion: YES

Toxicological data : There is no available data for the product itself, only for the ingredients. See

below for individual ingredient acute toxicity data.

	LC₅₀(4hr)	LD50		
<u>Ingredients</u>	<u>inh, rat</u>	<u>oral</u>	dermal	
aolin	N/Av	N/Av	N/Av	
rea	N/Av	8471 mg/kg (rat)	> 21,000 mg/kg (rabbit)	
tosin	N/Av	N/Av	N/Av	
olvent refined heavy araffinic distillate	N/Av	> 5000 mg/kg (rat)	> 5000 mg/kg (rabbit)	
vistillates (petroleum), olvent-refined	> 4000 mg/m³	> 5000 mg/kg (rat)	> 5000 mg/kg (rabbit)	
Frisodium phosphate	N/Av	4100 mg/kg (rat)	7940 mg/kg (rabbit)	

Carcinogenic status : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects: None known.Teratogenicity: None known.Mutagenicity: None known.Epidemiology: Not available.

Henry® 356C MultiPro™ Premium Commercial Multipurpose Carpet and Sheet Vinyl Adhesive

MSDS Revision Date (dd/mm/yyyy): 27/10/2009

Sensitization to material : May cause allergic respiratory reaction (sensitization) with asthmatic symptoms such as

wheezing and chest tightness. May cause severe skin sensitization with allergic contact

dermatitis symptoms such as swelling, rash and eczema.

Synergistic materials : N/Av Irritancy : Mild.

other important hazards : See Section 3 for additional information.

Conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity : No data is available on the product itself. The product should not be allowed to enter

drains or water courses, or be deposited where it can affect ground or surface waters.

Mobility: No data is available on the product itself.

Persistence : No data is available on the product itself.

Bioaccumulation potential : No data is available on the product itself.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle waste according to recommendations in Section 7.

Methods of Disposal : Dispose in accordance with all applicable federal, state, provincial and local

regulations. Contact your local, state, provincial or federal environmental agency for

specific rules.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the

criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and

federal environmental agencies.

SECTION 14 - TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	Not regulated.	not regulated	none	\otimes
TDG Additional information	None.				
49CFR/DOT	None	Not regulated.	not regulated	none	\otimes
49CFR/DOT Additional information	None.				

SECTION 15 - REGULATORY INFORMATION

Canadian Information:

Canadian Environmental Protection Act (CEPA): All components of this product are on the Canadian DSL list.

Canadian WHMIS Classification: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

US Federal Information:

Page 5 of 7

Page 6 of 7

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory. CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: This product contains a chemical known to the State of California to cause cancer. This product contains trace amounts of: Ethylbenzene; Crystalline silica, guartz.

Other U.S. State "Right to Know" Lists: The following chemicals are specifically listed by individual States: Kaolin (MA, MN, NJ, PA, RI); Urea (MN); Rosin (MN); Distillates (petroleum), solvent-refined (MA); Trisodium phosphate (CA, MA, MN, NJ, PA).

SECTION 16 - OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substances List EPA: Environmental Protection Agency

IARC: International Agency for Research on Cancer

LC: Lethal Concentration

LD: Lethal Dose MA: Massachusetts MN: Minnesota N/Av: Not Available N/Ap: Not Applicable

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit TLV: Threshold Limit Values TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WEEL: Workplace Environmental Exposure Level

WHMIS: Workplace Hazardous Materials Identification System

References

- 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2009.
- 2. International Agency for Research on Cancer Monographs, searched 2009.
- Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2009 (Chempendium, HSDB and RTECs).
- 4. Material Safety Data Sheets from manufacturer.
- 5. US EPA Title III List of Lists October 2006 version.
- 6. California Proposition 65 List September 11, 2009 version.

DISCLAIMER OF LIABILITY

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with

employed during the use of this product.

No warranty of any kind is given or implied. The W.W. Henry Company will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein. This Material Safety Data Sheet is valid for three (3) years.

any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures

Prepared By:

The W.W. Henry Company 400 Ardex Park Drive Aliquippa, PA, U.S.A. 15001 (724) 203-8499

Visit our Website: http://www.wwhenry.com
MSDS Preparation Date (dd/mm/yyyy)

: 23/08/2008

MSDS Reviewed Date (dd/mm/yyyy)

: 27/10/2009

Revision No. : 2

Revision Information: Sections 2 and 3, switched.

(M)SDS sections updated:

2. HAZARDS IDENTIFICATION:

- 3. COMPOSITION/INFORMATION ON INGREDIENTS;
- 5. FIRE-FIGHTING MEASURES;
- 8. EXPOSURE CONTROLS / PERSONAL PROTECTION;
- 9. PHYSICAL AND CHEMICAL PROPERTIES;
- 11. TOXICOLOGICAL INFORMATION;
- 12. ECOLOGICAL INFORMATION;
- 15. REGULATORY INFORMATION.

END OF DOCUMENT

Page 7 of 7