Product Name: Faucet & Valve Grease

ACUTE- SEE MEDICAL CONDITIONS BELOW

Signs and Symptoms:

#251603 MSDS No.: 050115 Part Numbers Covered 050005-30 050035-12 050050-D 050120 050010-12 050035-48 050053-12 050125 050035-C 050055-12 050190 050010-48 050050-12 050055-48 050200 050020 050025 050050-48 050060-48 050030 050050-C 050115 ik Bisicinamatan **NFPA** Manufacturer: WILLIAM H. HARVEY COMPANY Address: 4334 SOUTH 67TH STREET Reastivity City, ST Zip: OMAHA, NE 68117-1019 **Emergency Contact: CHEMTREC** Emergency Telephone Number: (800)424-9300 ipecja Contact: Ray Rael / Jason Hertz Information Telephone Number: (800)228-9681 Last Update: 07/08/2002 **Expiration Date:** 0 Reactivity X Solid **Chemical State:** Liquid В Pers. Protection Chemical Type: Pure Mixture H. Ingredients Trade Secret **EHS** IARC SARA **OSHA ACGIH** Other 313 SUB Z CAS No. % Range NTP PEL TLV Limits Chemical Name 8012951 NAPHTHENIC MINERAL OIL 80-97 5 MG/M3 5 MG/M3 NI III i i brandors i ribuiji caitas **Hazard Category:** Fire Acute Chronic Pressure Reactive Hazardous Identification Information: NDA W. Trusti Avil Marsima Route(s) of Entry: SKIN AND INHALATION Health Hazards (Acute and Chronic):

CHRONIC- LAB STUDIES IN WHICH MATERIALS SIMILAR TO SOME OF THE OILS IN THIS PRODUCT ARE APPLIED TO ANIMALS FOR THEIR LIFETIMES CAUSED TUMORS. AVOID THIS HAZARD BY USING GOOD PERSONAL HYGIENE.

Product Name: Faucet & Valve Grease

MSDS No.: 050115

GENERALLY NONE DURING SHORT PERIOD OF EXPOSURE.

Medical Conditions Generally Aggravated by Exposure:

SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE MILD IRRITATION.

INHALATION: MIST MAY CAUSE IRRITATION

Emergency and First Aid Procedures:

EMERGENCY FIRST AID CALL: 1-303-623-5716 COLLECT

EYES: FLUSH IMMEDIATELY WITH COLD WATER AND CALL A PHYSICIAN

SKIN: WASH EXPOSED AREA WITH SOAP AND WATER

INGESTION: DO NOT INDUCE VOMITING; CONTACT A PHYSICIAN IMMEDIATELY

Other Health Warnings:

NI

V. Thue Frighting Measures

Flash Point: 450 F DEG

Lower Explosive Limit: Ni

Upper Explosive Limit:

F.P. Method:

Fire Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, OR FOAM

Special Fire Fighting Procedures:

AVOID BREATHING VAPORS. USE BREATHING APPARATUS IN CONFINED AREAS.COOL EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire and Explosion:

NI

WK Asadbandtidense Menstress

Steps to be Taken in Case Material is Released or Spilled:

SCOOP UP MATERIAL AND PLACE IN TRASH CONTAINER; WASH DOWN SPILL AREA WITH SOAP AND WATER BUT KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES.

VIII. Is to allow and Storages

Precautions to be Taken:

KEEP CONTAINERS CLOSED WHEN NOT IN USE.. DO NOT HANDLE OR STORE NEAR HEAT, FLAMES, SPARKS, OR STRONG OXIDANTS. DO NOT WELD, HEAT, OR DRILL ON EMPTIED CONTAINERS.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN AND PETS!

Will. To governe Compole Personal Brandenous

Ventilation Requirements:

HAVE LOCAL EXHAUST AS NECESSARY TO PREVENT VAPOR BUILDUP

Personal Protective Equipment:

WEAR CHEMICALLY RESISTANT RUBBER GLOVES, APRON, COVERALLS, OR STANDARD WORK APPAREL, AND SAFETY GOGGLES ARE USEFUL. USE NORMAL GOOD SAFETY AND HEALTH PROCEDURES. REMOVE ANY CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE.

Product Name: Faucet & Valve Grease

MSDS No.: 050115

IE. - Physical amil Chemical Phyperiese

Boiling Point: NI

Melting Point: 170 C D

Evaporation Rate (Butyl Acetate = 1): >1.0

Vapor Pressure (mm Hg.): 0.1

Specific Gravity (H20 = 1): 1.00000

Vapor Density (AIR = 1): 1.0

Solubility In Water: NEGLIGIBLE

Appearance and Odor: SEMI-SOLID GEL, AMBER COLOR WITH MI

Other Information:

X Subility and Reactivity

Stability:

STABLE

Incompatibility (Materials to Avoid):

NI

Decomposition/By Products:

CARBON MONOXIDE, CARBON DIOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS

Hazardous Polymerization:

WILL NOT OCCUR

XII. Toxtealogical Italographics :

NDA

XII. Ecological information

NDA

ZIIII. Dispusal Consultrations.

DISPOSE OF ACCORDING TO APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS.

XIV. Thanspool Ingomation

TRANSPORATION INFORMATION:

DOT PROPER SHIPPING NAME: N/A

DOT LABEL: N/A DOT NUMBER: N/A UN NUMBER: N/A

MCO CLASS: N/A DOT HAZARD CLASSIFICATION: N/A

NDA

Product Name: Faucet & Valve Grease

MSDS No.: 050115

SAKA - Milioto Anging anging a

ABBREVIATIONS:

N/A = NOT APPLICABLE N/I = NONE INDICATED NDA = NO DATA AVAILABLE N/E = NOT ESTABLISHED C = CELSIUS DEGREES F = FAHRENHEIT DEGREES

DISCLAIMER:

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE, UP-TO-DATE, AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, WILLIAM H. HARVEY COMPANY CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE WARRANTIES, NOR ASSUMES ANY LIABILITY FOR ITS USES.