
# **Material Safety Data Sheet**

Prepared according to US OSHA, CMA, ANSI and Canadian WHMIS Standards.





# Section 1. Chemical product and company identification

Commercial name(s).

Nitrogen/ALIGAL ™ 1/ALIGAL WINE

MSDS no.

10070

Product use

Various/Special atmospheres for food.

Manufactured/supplied

**Address** 

2700 Post Oak Drive Houston, TX 77056-8229

**Emergency telephone** 

CHEMTREC: 1-800-424-9300

number

Telephone no.

1-(713)-896-2896 **GENERAL MSDS** 

INFORMATION

1-(800)-231-1366 Fax on Demand

## Section 2. Hazards identification

Physical state

: Gas.

**OSHA/HCS** status

This material is classified hazardous under OSHA regulations in the United States and

the WHMIS Controlled Product Regulation in Canada.

**Emergency overview** 

: CAUTION!

HIGH PRESSURE GAS. GAS REDUCES OXYGEN AVAILABLE FOR BREATHING. Keep away from heat (<52°C/125°F). Use only with adequate ventilation. Extremely hazardous gas under pressure. Keep cylinder valve closed when the product is not used.

Gas may accumulate in confined areas.

Routes of entry

Potential acute health effects

Inhalation

: Inhalation. Dermal contact. Eye contact.

: Inhalation of this product may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyxiation.

Skin Eyes : No known significant effects or critical hazards. : No known significant effects or critical hazards.

Ingestion

Since the product is a gas, it will probably be inhaled rather than ingested. See above.

Potential chronic health

effects

: Carcinogenic effects: Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Mutagenic effects: Not available. Teratogenic effects: Not available.

Over-exposure signs/symptoms

Inhalation

: No specific data.

Ingestion

: No specific data.

Skin

: No specific data.

**Eves** 

: No specific data.

: None known.

**Medical conditions** aggravated by over-

exposure

See toxicological information (section 11)

Date of issue Powered by



Page: 1/6 Powered by ATRION

### Nitrogen/ALIGAL ™ 1/ALIGAL WINE

# Section 3. Composition, Information on Ingredients

mole % CAS number

Canada Nitrogen

7727-37-9

> 99.99

#### **United States**

Chemical name Nitrogen	<b>CAS #</b> 7727-37-9	mole % > 99.99	Occupational exposure limits  There are no specific exposure limits for this gas.  This gas is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.	IDLH NE
---------------------------	------------------------	----------------	--	------------

**NE: Not Established** 

See Section 16 for possible acronym definitions

See Sections 8, 11, 14 and 15 for details.

## Section 4. First aid measures

Prompt medical attention is mandatory in all cases of overexposure to this gas. Rescue personnel should wear a self-contained breathing apparatus.

Inhalation

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical

attention if symptoms appear.

C: Ceiling Limit

Skin contact

Not applicable. : Not applicable.

Eye contact Ingestion

: Since the product is a gas, it will probably be inhaled rather than ingested. See above.

Notes to physician

: The medical doctor must be warned that the person may suffer from anoxia.

## Section 5. Fire fighting measures

Flammability of the product

: Non-flammable.

**Products of combustion** 

Decomposition products may include the following materials:

nitrogen oxides

Explosion hazards in the presence of various substances

: Container explosion may occur under fire conditions or when heated.

Fire-fighting media and instructions

: Use an extinguishing agent suitable for the surrounding fire.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers

Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions

EVACUATE ALL PERSONNEL FROM AFFECTED AREA.

Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. If leak is on cylinder or cylinder valve, contact the closest Air Liquide location.

**Environmental precautions** 

: 12/31/2007

: No special measures required.

Methods for cleaning up

: Contact your local Air Liquide Gas supplier for details.

Date of issue Powered by ATRION AIR LIQUIDE

Page: 2/6 Powered by ATRION

## Section 7. Handling and storage

#### Handling

: Valve protection caps must remain in place unless cylinder is secured with valve outlet piped to usage point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow to the cylinder. Do not tamper with (valve) safety device. Close valve after each use and when empty.

#### Storage

: Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non combustible construction away from heavy traffic areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 52°C/125°F. Cylinders must be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Prevent full cylinders being stored for excessive periods of time. Post "No Smoking or Open Flames" signs in the storage or use area. There should be no source of ignition in the storage or use area.

## Section 8. Exposure controls/personal protection

**Engineering controls** Personal protection

: Use only in well-ventilated areas.

Respiratory

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Wear leather gloves when handling cylinders of this gas. Otherwise, wear glove protection appropriate to the specific operation for which this gas is used.

Safety glasses with side shields.

Eyes

Skin/Body

: Use body protection appropriate for task. Cotton clothing is recommended for use to prevent static electric build-up. Pressurized product may require use of fire retardant

Metal cap, safety shoes are recommended when handling cylinders.











Some applications of this product may require additionnal or other specific protective clothings. Please consult your supervisor.

Personal protection in case of a major leak

: Safety glasses with side shields, goggles or face shield. Impervious gloves. Protective clothing. Metal cap, safety shoes. Wear MSHA/NIOSH-approved self-contained breathing apparatus or equivalent and full protective gear.

**Product name** Canada

**Exposure limits** 

Nitrogen

Simple asphyxiant. (NE)

**United States** Nitrogen

Simple asphyxiant. (NE)

**NE: Not Established** 

## Section 9. Physical and chemical properties

: Gas. Physical state

: Colorless. Color : Odorless. Odor : 28.02 g/mole Molecular weight

Molecular formula

: -195.79°C (-320.4°F) Boiling/condensation point

Date of issue Powered by ATRION



Page: 3/6

Powered by OTRION

: 12/31/2007

#### Nitrogen/ALIGAL ™ 1/ALIGAL WINE

: -209.99°C (-346°F) Melting/freezing point : -146.9°C (-232.4°F) **Critical temperature** : 0.97 (Air = 1) Specific gravity

## Section 10. Stability and reactivity

Stability and reactivity

The product is stable.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

: Under normal conditions of storage and use, hazardous polymerization will not occur. Hazardous polymerization

## Section 11. Toxicological information

**Acute Effects** 

: Inhalation of this product may cause dizziness, an irregular heartbeat, narcosis, nausea Inhalation

or asphyxiation.

: No known significant effects or critical hazards. Skin : No known significant effects or critical hazards. Eyes

: Since the product is a gas, it will probably be inhaled rather than ingested. See above. Ingestion Carcinogenic effects: Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Potential chronic health Mutagenic effects: Not available.

Teratogenic effects: Not available.

### Section 12. Ecological information

: These gases are released as is in the atmosphere. **Products of degradation** 

### Section 13. Disposal considerations

Disposal

effects

: Residual materials contained in customer-owned cylinders should be disposed of in accordance with Federal, State and Local regulations on waste management. For residual materials contained in cylinders owned by Air Liquide, contact Sales or Customer Service to determine appropriate disposal. Do not return cylinders without authorization from Air Liquide.

### 14. Transport information

: 12/31/2007

: 120 **AERG** 

Regulatory information	Proper shipping name	Class	UN number	PG	Label
UN / IMDG / IATA Classification	NITROGEN, COMPRESSED	2.2	UN1066	-	
DOT Classification	NITROGEN, COMPRESSED	2.2	UN1066	-	
TDG Classification	NITROGEN, COMPRESSED	2.2	UN1066	-	





Page: 4/6

Powered by ATRION

#### Nitrogen/ALIGAL ™ 1/ALIGAL WINE

Additional information UN

IMDG

IATA

TDG

Passenger and Cargo AircraftQuantity limitation: 75 kg

Limited quantity Yes.

Cargo Aircraft Only Quantity limitation: 150 kg

Packaging instruction Passenger aircraft Quantity limitation: 75 kg

Cargo aircraft Quantity limitation: 150

Cylinders should be transported in a secure position, in a well ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards and should be discouraged.

## Section 15. Regulatory information

Canada

WHMIS (Canada)

: Class A: Compressed gas.



Canada inventory: This material is listed or exempted.

CEPA DSL: All components listed.

**United States** 

OSHA HAZARD COMMUNICATION STANDARD (29CFR PART 1910.1200).

Compressed gas

SARA 302/304 emergency planning and notification: No products were found.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Nitrogen: Sudden release of pressure

CERCLA: Hazardous substances.: No products were found.

**US INVENTORY (TSCA)** 

TSCA 8(b) inventory: All components listed.

State regulations

California prop. 65: No products were found.

Connecticut Carcinogen Reporting: This material is not listed.

Connecticut Hazardous Material Survey: This material is not listed.

Florida substances: This material is not listed.

Illinois Chemical Safety Act: This material is not listed.

Illinois Toxic Substances Disclosure to Employee Act: This material is not listed.

Louisiana Reporting: This material is not listed.

Louisiana Spill: This material is not listed.

Massachusetts Spill: This material is not listed.

Massachusetts Substances: This material is listed.

Michigan Critical Material: This material is not listed.

Minnesota Hazardous Substances: This material is not listed.

New Jersey Hazardous Substances: This material is listed.

New Jersey Spill: This material is not listed.

12/31/2007

New Jersey Toxic Catastrophe Prevention Act: This material is not listed.

New York Acutely Hazardous Substances: This material is not listed.

New York Toxic Chemical Release Reporting: This material is not listed.

Pennsylvania RTK Hazardous Substances: This material is listed.

Rhode Island Hazardous Substances: This material is not listed.





Page: 5/6 Powered by ATRION

### **Section 16. Other information**

**Hazardous Material** Information System (U.S.A.)

1 Health 0 Fire hazard 0 Reactivity G Personal protection

**National Fire Protection** Association (U.S.A.)



Consult an Industrial Hygienist or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

Further information about gas mixtures can be found in pamphlets published by: Compressed Gas Association Inc (CGA), 4221 Walney Road, 5th floor, Chantilly, VA 20151-2923 Telephone: (703) 788-2700.

: ACGIH: American Conference of Governmental Industrial Hygiene. **Acronyms** 

IARC: International Agency for Research on Cancer. NIOSH: National Institute of Occupational Safety and Health. OSHA: Occupational Safety and Health Administration

NTP: National Toxicology program.

OECD: Organisation for Economic Co-operation and Development.

PEL: Permissible Exposure Limit.

IDLH: Immediately Dangerous to Life and Health.

NE: Not established. C: Ceiling Limit.

**DSL: Domestic Substance List.** NDSL: Non-Domestic Substance List. CFR: Code of Federal Regulations. TSCA: Toxic Substance Control Act.

: 12/31/2007 Date of issue Date of previous issue 04/25/2002

: 12/31/2007

Version

Notice to reader

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200, American National Standard Institute Z400.1, 2004, the Canadian Workplace Hazardous Material Information Systems (WHMIS). Other government regulations must be reviewed for applicability to this gas mixture. To the best of Air Liquide's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

: ALIGAL™ : Trademark of L'Air Liquide S.A. **Trademarks** 





Page: 6/6